

View Online at <https://aerobasegroup.com/nsn/5962-01-370-8088>

Body Length:

Between 1.580 inches and 1.700 inches

Body Width:

Between 0.580 inches and 0.605 inches

Body Height:

Between 0.129 inches and 0.230 inches

Maximum Power Dissipation Rating:

1.0 watts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Monolithic and electrostatic sensitive and low power and burn in, mil-std-883, class b

Inclosure Material:

Ceramic or glass

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Complementary-metal oxide-semiconductor logic

Terminal Surface Treatment:

Solder

Product Name:

Microcircuit, memory, digital, cmos 128k x 8 static random access memor (scram) low power, monolithic silicon

Voltage Rating And Type Per Characteristic:

-0.5 volts total supply and 7.0 volts total supply

Time Rating Per Characteristic:

55.00 nanoseconds access

Memory Device Type:

Ram

Hybrid Technology Type:

Monolithic

Test Data Document:

81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And 81349-mil-i-38535 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And 96906-mil-std-480 standard (includes industry or association standards, individual manufactureer standards, etc.). And 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

32 printed circuit

Specification Data:

67268-5962-89598 government standard

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A458a0