## NSN 5962-01-371-1030

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-371-1030

| View Online at https://aerobasegroup.com/nsn/5962-01-371-1030   |
|---|
| Body Length:  |
| 1.490 inches  |
| Body Width:   |
| Between 0.500 inches and 0.610 inches   |
| Body Height:  |
| 0.217 inches  |
| Maximum Power Dissipation Rating:   |
| 1.0 watts   |
| Operating Tempurature Range:  |
| -55.0/+125.0 degrees celsius  |
| Storage Tempurature Range:  |
| -65.0/+150.0 degrees celsius  |
| Features Provided:  |
| Monolithic and w/clock and w/reset  |
| Inclosure Material:   |
| Ceramic   |
| Inclosure Configuration:  |
| Dual-in-line Dual-in-line   |
| Output Logic Form:  |
| Complementary-metal oxide-semiconductor logic   |
| Input Circuit Pattern:  |
| 12 input  |
| Case Outline Source And Designator:   |
| D-10 mil-m-38510  |
| Current Rating Per Characteristic:  |
| 150.00 milliamperes reverse current, dc absolute  |
| Terminal Surface Treatment:   |
| Solder  |
| Voltage Rating And Type Per Characteristic:   |
| -0.5 volts power source and 7.0 volts power source  |
| Capitance Rating Per Characteristic:  |
| 8.00 input picofarads and 12.00 output picofarads   |
| Time Rating Per Chacteristic:   |
| 65.00 nanoseconds access  |
| Memory Device Type:   |
| First-in first-out  |
| Test Data Document:   |
| 96906-mil-std-883  standard (includes industry or association standards, individual manufactureer standards, etc.). |
| Terminal Type And Quantity:   |
| 28 printed circuit  |
| Shelf Life:   |

N/a

## NSN 5962-01-371-1030

Memory Microcircuit - Page 2 of 2



|    | • • |             |    |     |      |
|----|-----|-------------|----|-----|------|
| In | 18  | <i>(</i> )+ | МА | 261 | ıre: |
|    |     |             |    |     |      |

--

Demilitarization:

No

Fiig:

A458a0