

View Online at <https://aerobasegroup.com/nsn/5962-01-371-5405>

Maximum Power Dissipation Rating:

1.2 watts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

End Application:

Enditem e/i fscm 03950

Features Provided:

Bipolar and monolithic and programmed

Inclosure Material:

Ceramic

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Bipolar metal-oxide semiconductor

Input Circuit Pattern:

22 input

Case Outline Source And Designator:

D-9 mil-m-38510

Current Rating Per Characteristic:

100.00 milliamperes reverse current, dc

Terminal Surface Treatment:

Solder

Product Name:

Microcircuit, bipolar pal, 22-input 10-output registered and-or logic array

Voltage Rating And Type Per Characteristic:

-0.5 volts absolute input and 5.5 volts absolute input

Memory Device Type:

Pal

Hybrid Technology Type:

Monolithic

Test Data Document:

81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And 96906-mil-std standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

24 printed circuit

Specification Data:

67268-5962-86053011a government standard

Purchase Description Identification:

05869-53192-1

Departure From Cited Designator:

Altered by programming, testing & marking

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0