

View Online at <https://aerobasegroup.com/nsn/5962-01-371-9495>

Maximum Power Dissipation Rating:

600.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

End Application:

5945-01-363-9030

Inclosure Configuration:

Dual-in-line

Design Function And Quantity:

1 microprocessor

Case Outline Source And Designator:

D-2 mil-m-38510

Current Rating Per Characteristic:

200.00 milliamperes reverse current, dc microamperes

Product Name:

Microcircuit, linear, supervisory circuit, microprocessor

Voltage Rating And Type Per Characteristic:

-0.3 volts applied and 6.0 volts applied

Test Data Document:

81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

16 printed circuit

Specification Data:

01365-87001f1305 government specification

Specification Or Standard:

01 type and e case and a finish

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0