

View Online at <https://aerobasegroup.com/nsn/5962-01-371-9500>

Body Length:

Between 0.342 inches and 0.358 inches

Body Width:

Between 0.342 inches and 0.358 inches

Body Height:

Between 0.060 inches and 0.100 inches

Maximum Power Dissipation Rating:

500.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

Features Provided:

3-state output and monolithic and burn in and w/enable and w/disable

Inclosure Material:

Ceramic

Inclosure Configuration:

Leadless flat pack

Output Logic Form:

Complementary-metal oxide-semiconductor logic

Input Circuit Pattern:

Dual 4 input

Criticality Code Justification:

Feat

Design Function And Quantity:

2 buffer and 2 driver, line

Case Outline Source And Designator:

C-2 mil-m-38510

Current Rating Per Characteristic:

1.00 microamperes reverse current, dc microamperes

Terminal Surface Treatment:

Solder

Product Name:

Octal inverting buffer/line driver

Voltage Rating And Type Per Characteristic:

-0.5 volts power source and 6.0 volts power source

Capitance Rating Per Characteristic:

10.00 input picofarads and 15.00 output picofarads

Time Rating Per Characteristic:

9.50 nanoseconds propagation delay time, high to low level output and 9.50 nanoseconds propagation delay time, low to high level output

Special Features:

Nuclear hardness critical item

Terminal Type And Quantity:

20 leadless

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A458a0