NSN 5962-01-372-1242



Digital Microcircuit - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5962-01-372-1242 **Body Length:** 1.290 inches **Body Width:** 0.310 inches **Body Height:** Between 0.015 inches and 0.060 inches **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **End Application:** Milstar **Features Provided:** Electrostatic sensitive and hermetically sealed and selected item and tested to mil-std-883 **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Transistor-transistor logic **Criticality Code Justification:** Feat **Design Function And Quantity:** 2 register, buffer **Product Name:** Microcircuit, digital, register **Voltage Rating And Type Per Characteristic:** 0.5 volts total supply and 7.0 volts total supply **Special Features:** Esd; hci; hermatically sealed, selected item, rescreened per 995-9501020-using 95105-0251-010; vender p/n am29823a/bla, goes to smd 5962-8775502la; nsn 013363735; noninvertingbuffer **Nuclear Hardness Critical Feature:** Hardened **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 24 printed circuit Shelf Life: N/a

Demilitarization: Yes - demil/mli

Unit Of Measure:

NSN 5962-01-372-1242

Digital Microcircuit - Page 2 of 2



Fiig:

A458a0