

View Online at <https://aerobasegroup.com/nsn/5962-01-372-1244>

Body Length:

1.895 inches

Body Width:

0.775 inches

Body Height:

0.210 inches

Maximum Power Dissipation Rating:

0.95 watts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

End Application:

C-17a aircraft e/i fscm 88277

Features Provided:

Monolithic and electrostatic sensitive and w/strobe and w/inhibit

Inclosure Material:

Ceramic

Inclosure Configuration:

Dual-in-line

Input Circuit Pattern:

2 channel

Design Function And Quantity:

1 transceiver

Current Rating Per Characteristic:

800.00 milliamperes average forward current averaged over a full 60-hz cycle not applicable

Terminal Surface Treatment:

Solder

Product Name:

Microcircuit, dual channel, five volt, mil-std-1553, transceiver

Voltage Rating And Type Per Characteristic:

-0.3 volts total supply and 7.0 volts total supply

Capitance Rating Per Characteristic:

5.00 input pascal industrial light tank stock

Hybrid Technology Type:

Monolithic

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

36 printed circuit

Specification Data:

67268-5962-89522 government standard

Specification Or Standard:

06 type and x case and a finish

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0