

View Online at <https://aerobasegroup.com/nsn/5962-01-372-1263>

Body Length:

1.250 inches

Body Width:

Between 0.350 inches and 0.410 inches

Body Height:

0.210 inches

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

Features Provided:

W/enable and w/reset and monolithic and w/disable

Inclosure Material:

Ceramic

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Transistor-transistor logic

Input Circuit Pattern:

15 input

Case Outline Source And Designator:

D-11 mil-m-38510

Current Rating Per Characteristic:

170.00 milliamperes reverse current, dc absolute

Terminal Surface Treatment:

Solder

Product Name:

Fifo buffer memory

Voltage Rating And Type Per Characteristic:

7.0 volts power source

Time Rating Per Characteristic:

54.00 nanoseconds propagation delay time, high to low level output and 68.00 nanoseconds propagation delay time, low to high level output

Memory Device Type:

First-in first-out

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

24 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A458a0