

View Online at <https://aerobasegroup.com/nsn/5962-01-372-4196>

**Body Length:**

Between 0.940 inches and 0.960 inches

**Body Width:**

Between 0.290 inches and 0.310 inches

**Body Height:**

Between 0.180 inches and 0.200 inches

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**End Application:**

Milstar

**Features Provided:**

Compatible cmos and burn in, mil-std-883, class b and electrostatic sensitive and cascable and radiation hardened and tested to mil-std-883 and selected item

**Inclosure Material:**

Ceramic

**Inclosure Configuration:**

Dual-in-line

**Output Logic Form:**

Complementary-metal oxide-semiconductor logic

**Criticality Code Justification:**

Feat

**Case Outline Source And Designator:**

D-6 mil-m-38510

**Terminal Surface Treatment:**

Solder

**Product Name:**

Microcircuit, digital, fifo

**Voltage Rating And Type Per Characteristic:**

-0.5 volts total supply and 7.0 volts total supply

**Memory Device Type:**

First-in first-out

**Special Features:**

Delectrostatic discharge sens/hardness critical item; selected item made from pn rc258-0107-020 cage 95105, which is rescreened from pn 995-9501-020 cage 95105 which is pn idt72404115dbrt cage 61772

**Special Test Features:**

Selected item qualified by total dose irradiation and verified for wafer lot hardness

**Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Terminal Type And Quantity:**

18 pin

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A458a0