

View Online at <https://aerobasegroup.com/nsn/5962-01-372-5016>

Maximum Power Dissipation Rating:

500.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Low drift and internally compensated

Inclosure Material:

Ceramic

Inclosure Configuration:

Leaded chip carrier

Input Circuit Pattern:

2 input

Design Function And Quantity:

1 amplifier, operational, analog

Case Outline Source And Designator:

C-2 mil-m-38510

Terminal Surface Treatment:

Solder

Product Name:

Microcircuit, linear, low offset operational amplifier

Voltage Rating And Type Per Characteristic:

-22.0 volts total supply and 22.0 volts total supply

Test Data Document:

81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

20 printed circuit

Specification Data:

81349--38510/135 government specification

Specification Or Standard:

02 type and b class and 2 case and a finish

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0