

View Online at <https://aerobasegroup.com/nsn/5962-01-372-6629>

**Body Length:**

Between 1.260 inches and 1.280 inches

**Body Width:**

Between 0.180 inches and 0.200 inches

**Body Height:**

Between 0.290 inches and 0.310 inches

**Maximum Power Dissipation Rating:**

1.2 watts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**End Application:**

Eolorops

**Features Provided:**

Electrostatic sensitive and burn in, mil-std-883, class b and monolithic and ultraviolet erasable and tested to mil-std-883 and programmed

**Inclosure Material:**

Ceramic

**Inclosure Configuration:**

Dual-in-line

**Output Logic Form:**

Complementary-metal oxide-semiconductor logic

**Input Circuit Pattern:**

22 input

**Criticality Code Justification:**

Feat

**Case Outline Source And Designator:**

D-9 mil-m-38510

**Terminal Surface Treatment:**

Solder

**Product Name:**

Microcircuit, programmed

**Voltage Rating And Type Per Characteristic:**

0.5 volts total supply and 7.0 volts total supply

**Time Rating Per Characteristic:**

25.00 nanoseconds af output megawatts

**Memory Device Type:**

Pal

**Special Features:**

Esd; checksum d0ee; filename; 1062u15.Jed; altered item using 67268, 59628753901lx

**Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Terminal Type And Quantity:**

24 printed circuit

**Specification Data:**

67268-5962-87539 government standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A458a0