NSN 5962-01-372-8213

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-372-8213

view Online at https://aerobasegroup.com/hsh/5962-01-372-6213
Body Length:
Between 1.440 inches and 1.490 inches
Body Width:
Between 0.590 inches and 0.620 inches
Body Height:
Between 0.030 inches and 0.180 inches
Maximum Power Dissipation Rating:
250.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Static operation and high speed and high performance and high reliability and low power and bidirectional and w/enable
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Complementary-metal oxide-semiconductor logic
Input Circuit Pattern:
25 input
Current Rating Per Characteristic:
90.00 milliamperes reverse current, dc absolute
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
-0.5 volts power source and 7.0 volts power source
Capitance Rating Per Characteristic:
8.00 input picofarads and 8.00 output picofarads
Time Rating Per Chacteristic:
55.00 nanoseconds access
Memory Device Type:
Ram
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
28 printed circuit
Shelf Life:
N/a

--

Unit Of Measure:

NSN 5962-01-372-8213

Memory Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0