NSN 5962-01-372-9754

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-372-9754

Body Outside Diameter:
Between 0.350 inches and 0.370 inches
Body Height:
Between 0.165 inches and 0.185 inches
Maximum Power Dissipation Rating:
330.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
Milstar
Features Provided:
Electrostatic sensitive and tested to mil-std-883 and burn in, mil-std-883, class b and monolithic and radiation hardened
Inclosure Material:
Ceramic
Inclosure Configuration:
Can
Criticality Code Justification:
Feat
Design Function And Quantity:
8 comparator
Case Outline Source And Designator:
A-1 mil-m-38510
Terminal Surface Treatment:
Solder
Product Name:
Microcircuit, linear, comparator
Voltage Rating And Type Per Characteristic:
15.0 volts total supply
Special Features:
Esd; hci
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
8 leadless
Specification Data:
8134938510/10304bga government specification
Shelf Life:
N/a
Unit Of Measure:

--

NSN 5962-01-372-9754

Linear Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0