

View Online at <https://aerobasegroup.com/nsn/5962-01-372-9998>

**Body Length:**

Between 0.750 inches and 0.830 inches

**Body Width:**

Between 0.240 inches and 0.310 inches

**Body Height:**

Between 0.030 inches and 0.185 inches

**Maximum Power Dissipation Rating:**

0.5 watts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**Features Provided:**

Presetable and high speed and w/enable and asynchronous and w/reset

**Inclosure Material:**

Ceramic

**Inclosure Configuration:**

Dual-in-line

**Output Logic Form:**

Complementary-metal oxide-semiconductor logic

**Input Circuit Pattern:**

9 input

**Design Function And Quantity:**

1 counter, binary

**Current Rating Per Characteristic:**

12.75 milliamperes reverse current, dc absolute

**Terminal Surface Treatment:**

Solder

**Voltage Rating And Type Per Characteristic:**

-0.5 volts power source and 7.0 volts power source

**Capitance Rating Per Characteristic:**

10.00 input picofarads and 12.00 output picofarads

**Time Rating Per Chacteristic:**

7.50 nanoseconds propagation delay time, high to low level output and 7.50 nanoseconds propagation delay time, low to high level output

**Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Terminal Type And Quantity:**

16 printed circuit

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A458a0