## NSN 5962-01-373-0568

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-373-0568

| 3.04  |
|---|
| Body Length:  |
| 1.490 inches  |
| Body Width:   |
| Between 0.500 inches and 0.610 inches   |
| Body Height:  |
| 0.217 inches  |
| Maximum Power Dissipation Rating:   |
| 1.0 watts   |
| Operating Tempurature Range:  |
| -55.0/+125.0 degrees celsius  |
| Storage Tempurature Range:  |
| -65.0/+150.0 degrees celsius  |
| Features Provided:  |
| Electrostatic sensitive and high impedance and w/disable and w/enable and ultraviolet erasable and programmed and w/buffered output |
| Inclosure Material:   |
| Ceramic   |
| Inclosure Configuration:  |
| Dual-in-line  |
| Output Logic Form:  |
| Transistor-transistor logic   |
| Input Circuit Pattern:  |
| 17 input  |
| Case Outline Source And Designator:   |
| D-10 mil-m-38510  |
| Current Rating Per Characteristic:  |
| 125.00 milliamperes reverse current, dc absolute  |
| Terminal Surface Treatment:   |
| Solder  |
| Voltage Rating And Type Per Characteristic:   |
| -0.6 volts power source and 6.25 volts power source   |
| Capitance Rating Per Characteristic:  |
| 6.00 input picofarads and 12.00 output picofarads   |
| Time Rating Per Chacteristic:   |
| 250.00 nanoseconds access   |
| Memory Device Type:   |
| Eprom   |
| Test Data Document:   |
| 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).                  |
| Terminal Type And Quantity:   |
| 28 printed circuit  |

N/a

Shelf Life:

## NSN 5962-01-373-0568

Memory Microcircuit - Page 2 of 2



|  |  |  | ure: |  |
|--|--|--|------|--|
|  |  |  |      |  |
|  |  |  |      |  |

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0