NSN 5962-01-373-0570

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-373-0570

view Online at https://aerobasegroup.com/nsn/5962-01-373-0570
Body Length:
Between 1.635 inches and 1.680 inches
Body Width:
Between 0.565 inches and 0.605 inches
Body Height:
Between 0.100 inches and 0.205 inches
Maximum Power Dissipation Rating:
350.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Ultraviolet erasable and w/inhibit and w/disable and bidirectional
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Complementary-metal oxide-semiconductor logic
Input Circuit Pattern:
20 input
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
-0.6 volts power source and 7.0 volts power source
Capitance Rating Per Characteristic:
12.00 input picofarads and 15.00 output picofarads
Time Rating Per Chacteristic:
250.00 nanoseconds access
Memory Device Type:
Eprom
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
32 printed circuit
Shelf Life:
N/a
Unit Of Measure:

Demilitarization: Yes - demil/mli

NSN 5962-01-373-0570

Memory Microcircuit - Page 2 of 2



Fiig:

A458a0