

View Online at <https://aerobasegroup.com/nsn/5962-01-373-1918>

**Body Length:**

Between 1.040 inches and 1.060 inches

**Body Width:**

Between 0.290 inches and 0.310 inches

**Body Height:**

Between 0.180 inches and 0.200 inches

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**End Application:**

Milstar

**Features Provided:**

Bipolar and electrostatic sensitive and monolithic and low power and radiation hardened and selected item and w/enable and 3-state output

**Inclosure Material:**

Ceramic

**Inclosure Configuration:**

Dual-in-line

**Output Logic Form:**

Transistor-transistor logic

**Input Circuit Pattern:**

10 input

**Criticality Code Justification:**

Feat

**Design Function And Quantity:**

8 transceiver

**Case Outline Source And Designator:**

D-8 mil-m-38510

**Terminal Surface Treatment:**

Solder

**Product Name:**

Microcircuit, digital, bus transceiver; microcircuit, rescreened

**Voltage Rating And Type Per Characteristic:**

-0.5 volts power source and 7.0 volts power source

**Special Features:**

Selected item, made from pn 258-0135-010, rescreened per 995-9501-020 and is pn 84003001rx

**Nuclear Hardness Critical Feature:**

Hardened

**Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufacturer standards, etc.).

**Terminal Type And Quantity:**

20 printed circuit

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A458a0