NSN 5962-01-373-3164

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-373-3164

Body Length:
0.220 inches
Body Outside Diameter:
0.650 inches
Maximum Power Dissipation Rating:
275.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
Milstar
Features Provided:
Tested to mil-std-883 and burn in, mil-std-883, class b and electrostatic sensitive and radiation hardened and selected item
Inclosure Material:
Metal
Inclosure Configuration:
Can
Input Circuit Pattern:
1 input
Criticality Code Justification:
Feat
Design Function And Quantity:
1 amplifier, limiter
Case Outline Source And Designator:
To-8 joint electron device engineering council
Current Rating Per Characteristic:
50.00 milliamperes reverse current, dc absolute
Terminal Surface Treatment:
Solder
Product Name:
Microcircuit, rescreened; microcircuit, limiting amplifier
Voltage Rating And Type Per Characteristic:
5.0 volts power source
Special Features:
Esd; hci; selected item 95105/252-0032-010 (which is 60979/sl847) has been rescreened per 95105/995-9501-020
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
4 pin
Shelf Life:
N/a

NSN 5962-01-373-3164

Linear Microcircuit - Page 2 of 2



	Of			

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0