NSN 5962-01-373-5193

Memory Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-373-5193

| Maximum Power Dissipation Rating: |
|--|
| 1.0 watts |
| Operating Tempurature Range: |
| -55.0/+125.0 degrees celsius |
| Storage Tempurature Range: |
| -65.0/+150.0 degrees celsius |
| Features Provided: |
| Burn in and electrostatic sensitive and programmed and ultraviolet erasable |
| Inclosure Material: |
| Ceramic |
| Inclosure Configuration: |
| Dual-in-line |
| Input Circuit Pattern: |
| 15 input |
| Case Outline Source And Designator: |
| D-10 mil-m-38510 |
| Terminal Surface Treatment: |
| Solder |
| Voltage Rating And Type Per Characteristic: |
| -0.3 volts power source and 7.0 volts power source |
| Time Rating Per Chacteristic: |
| 250.00 nanoseconds access |
| Memory Device Type: |
| Rom |
| Test Data Document: |
| $96906 \hbox{-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.)}.$ |
| Terminal Type And Quantity: |
| 28 printed circuit |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |
| Fiig: |
| A458a0 |
| |