

View Online at <https://aerobasegroup.com/nsn/5962-01-373-5204>

Body Length:

Between 1.260 inches and 1.280 inches

Body Width:

Between 0.290 inches and 0.310 inches

Body Height:

Between 0.180 inches and 0.200 inches

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

End Application:

Eo lorops

Features Provided:

Burn in and compatible cmos and erasable and electrostatic sensitive and programmed and hermetically sealed and w/clock

Inclosure Material:

Ceramic

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Complementary-metal oxide-semiconductor logic

Input Circuit Pattern:

22 input

Criticality Code Justification:

Feat

Case Outline Source And Designator:

D-9 mil-m-38510

Terminal Surface Treatment:

Solder

Product Name:

Microcircuit, programmed

Voltage Rating And Type Per Characteristic:

-2.0 volts power source and 7.0 volts power source

Time Rating Per Characteristic:

55.00 nanoseconds propagation delay time, high to low level output and 55.00 nanoseconds propagation delay time, low to high level output

Memory Device Type:

Pal

Special Features:

Electrostatic discharge sensitive; altered item, made from 5962-8686401la, programmed per 1058-u37.Jed, fd137200104-001, checksum 36c6; nha pn 1372ae1058

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

24 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0