

View Online at <https://aerobasegroup.com/nsn/5962-01-373-5206>

**Body Length:**

Between 1.260 inches and 1.280 inches

**Body Width:**

Between 0.290 inches and 0.310 inches

**Body Height:**

Between 0.180 inches and 0.200 inches

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**End Application:**

Eo lorops

**Features Provided:**

Burn in and compatible cmos and erasable and electrostatic sensitive and programmed and hermetically sealed and w/clock

**Inclosure Material:**

Ceramic

**Inclosure Configuration:**

Dual-in-line

**Output Logic Form:**

Complementary-metal oxide-semiconductor logic

**Input Circuit Pattern:**

22 input

**Criticality Code Justification:**

Feat

**Case Outline Source And Designator:**

D-9 mil-m-38510

**Terminal Surface Treatment:**

Solder

**Product Name:**

Microcircuit, programmed

**Voltage Rating And Type Per Characteristic:**

-2.0 volts power source and 7.0 volts power source

**Time Rating Per Characteristic:**

55.00 nanoseconds propagation delay time, high to low level output and 55.00 nanoseconds propagation delay time, low to high level output

**Memory Device Type:**

Pal

**Special Features:**

Electrostatic discharge sensitive; altered item, made from 5962-8686401la, programmed per 1058-u10.Jed, fd137200067-001, checksum 188f; nha pn 1372ae1058

**Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Terminal Type And Quantity:**

24 printed circuit

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A458a0