## NSN 5962-01-373-7112

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-373-7112

## **Body Length:**

Between 0.925 inches and 1.060 inches

## Body Width:

Between 0.240 inches and 0.280 inches

## **Body Height:**

Between 0.115 inches and 0.195 inches

## **Maximum Power Dissipation Rating:**

500.0 milliwatts

## **Operating Tempurature Range:**

+0.0/+70.0 degrees celsius

## Storage Tempurature Range:

-65.0/+150.0 degrees celsius

## **End Application:**

6625-01-276-5446 test set, modem

## **Features Provided:**

3-state output and w/enable and high impedance and monolithic

## Inclosure Material:

Plastic

## Inclosure Configuration:

Dual-in-line

## Output Logic Form:

Complementary-metal oxide-semiconductor logic

## Input Circuit Pattern:

10 input

## **Design Function And Quantity:**

8 latch

## **Current Rating Per Characteristic:**

100.00 milliamperes reverse current, dc absolute

## **Terminal Surface Treatment:**

Solder

## **Product Name:**

Non-inverting octal transparent latch

## Voltage Rating And Type Per Characteristic:

-0.5 volts power source and 6.0 volts power source

## **Capitance Rating Per Characteristic:**

10.00 input picofarads and 15.00 output picofarads

## **Terminal Type And Quantity:**

20 printed circuit

Shelf Life:

N/a

#### Unit Of Measure:

--

# NSN 5962-01-373-7112

Digital Microcircuit - Page 2 of 2

## Demilitarization:

Yes - demil/mli

Fiig:

A458a0

