## NSN 5962-01-373-9123

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-373-9123

View Online at https://aerobasegroup.com/nsn/5962-01-373-9123
Body Length:
Between 1.180 inches and 1.235 inches
Body Width:
Between 1.180 inches and 1.235 inches
Body Height:
Between 0.077 inches and 0.145 inches
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Low power and cascadable and asynchronous and high speed and bidirectional and w/enable
Inclosure Material:
Ceramic
Inclosure Configuration:
Pin grid array
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
27 input and 50 input
Current Rating Per Characteristic:
50.00 milliamperes average forward current averaged over a full 60-hz cycle not applicable
Terminal Surface Treatment:
Solder
Product Name:
Dual-port static ram
Voltage Rating And Type Per Characteristic:
-0.5 volts power source and 7.0 volts power source
Capitance Rating Per Characteristic:
11.00 input picofarads and 11.00 output picofarads
Time Rating Per Chacteristic:
45.00 nanoseconds access
Memory Device Type:
Ram
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.)
Terminal Type And Quantity:
84 pin
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 5962-01-373-9123

Memory Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0