NSN 5962-01-374-0042

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-374-0042

| Operating Tempurature Range: -40.0/+85.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius End Application: 6625-01-276-5446 Features Provided: Wideband and high frequency Inclosure Material: Plastic Inclosure Configuration: |
|---|
| Inclosure Configuration: |
| -40.0/+85.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius End Application: 6625-01-276-5446 Features Provided: Wideband and high frequency Inclosure Material: Plastic Inclosure Configuration: |
| Storage Tempurature Range: -65.0/+150.0 degrees celsius End Application: 6625-01-276-5446 Features Provided: Wideband and high frequency Inclosure Material: Plastic Inclosure Configuration: |
| -65.0/+150.0 degrees celsius End Application: 6625-01-276-5446 Features Provided: Wideband and high frequency Inclosure Material: Plastic Inclosure Configuration: |
| End Application: 6625-01-276-5446 Features Provided: Wideband and high frequency Inclosure Material: Plastic Inclosure Configuration: |
| 6625-01-276-5446 Features Provided: Wideband and high frequency Inclosure Material: Plastic Inclosure Configuration: |
| Features Provided: Wideband and high frequency Inclosure Material: Plastic Inclosure Configuration: |
| Wideband and high frequency Inclosure Material: Plastic Inclosure Configuration: |
| Inclosure Material: Plastic Inclosure Configuration: |
| Plastic Inclosure Configuration: |
| Plastic Inclosure Configuration: Dual-in-line |
| |
| Dual-in-line |
| - vo |
| Input Circuit Pattern: |
| 1 input |
| Design Function And Quantity: |
| 1 amplifier, wideband |
| Current Rating Per Characteristic: |
| 25.00 milliamperes collector cutoff current, dc, emitter open any acceptable and 33.00 milliamperes peak forward surge current a |
| acceptable |
| Terminal Surface Treatment: |
| Solder |
| Product Name: |
| Wide-band high-frequency amplifier |
| Voltage Rating And Type Per Characteristic: |
| 9.0 volts total supply and 5.0 volts absolute input |
| Special Features: |
| Small outline package |
| Terminal Type And Quantity: |
| 8 printed circuit |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |
| Fiig: |
| A458a0 |