

View Online at <https://aerobasegroup.com/nsn/5962-01-374-0046>

Maximum Power Dissipation Rating:

3.025 watts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Monolithic

Inclosure Configuration:

Pin grid array

Design Function And Quantity:

3 converter, digital to analog

Case Outline Source And Designator:

P-bd mil-m-38510

Terminal Surface Treatment:

Solder

Product Name:

Triple, 8-bit d/a converter

Voltage Rating And Type Per Characteristic:

7.0 volts total supply

Special Features:

Converter contains a 256 x 24 color palette

Test Data Document:

81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

84 printed circuit

Specification Data:

67268-5962-89928 government standard

Specification Or Standard:

01 type and x case and a finish

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0