NSN 5962-01-374-0073

Digital-linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-374-0073 **Body Length:** 1.490 inches **Body Width:** Between 0.500 inches and 0.610 inches **Body Height:** 0.210 inches **Maximum Power Dissipation Rating:** 1.0 watts **Operating Tempurature Range:** -55.0 to 125.0 degrees celsius Storage Tempurature Range: -65.0 to 150.0 degrees celsius **Features Provided:** Low drift and low power and low noise and bipolar and high precision and electrostatic sensitive and monolithic **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Bipolar metal-oxide semiconductor **Input Circuit Pattern:** 20 input **Design Function And Quantity:** 1 converter, digital to analog **Current Rating Per Characteristic:** 13.00 milliamperes supply **Terminal Surface Treatment:** Solder **Product Name:** Monotonic voltage output d/a converter **Voltage Rating And Type Per Characteristic:** -18.0 volts power source and 18.0 volts power source **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 28 printed circuit Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

Yes - demil/mli

NSN 5962-01-374-0073

Digital-linear Microcircuit - Page 2 of 2



Fiig:

A458a0