## NSN 5962-01-374-0719

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-374-0719

Between 0.335 inches and 0.375 inches  Body Height:  Between 0.165 inches and 0.185 inches  Maximum Power Dissipation Rating: 350.0 milliwatts  Operating Tempurature Range: -55.0/+125.0 degrees celsius  Storage Tempurature Range: -65.0/+150.0 degrees celsius  Features Provided: Internally compensated and hermetically sealed and monolithic and electrostatic sensitive  Inclosure Material:  Metal
Body Height: Between 0.165 inches and 0.185 inches  Maximum Power Dissipation Rating: 350.0 milliwatts  Operating Tempurature Range: -55.0/+125.0 degrees celsius  Storage Tempurature Range: -65.0/+150.0 degrees celsius  Features Provided: Internally compensated and hermetically sealed and monolithic and electrostatic sensitive Inclosure Material:
Between 0.165 inches and 0.185 inches  Maximum Power Dissipation Rating: 350.0 milliwatts  Operating Tempurature Range: -55.0/+125.0 degrees celsius  Storage Tempurature Range: -65.0/+150.0 degrees celsius  Features Provided: Internally compensated and hermetically sealed and monolithic and electrostatic sensitive Inclosure Material:
Maximum Power Dissipation Rating: 350.0 milliwatts  Operating Tempurature Range: -55.0/+125.0 degrees celsius  Storage Tempurature Range: -65.0/+150.0 degrees celsius  Features Provided: Internally compensated and hermetically sealed and monolithic and electrostatic sensitive Inclosure Material:
350.0 milliwatts  Operating Tempurature Range: -55.0/+125.0 degrees celsius  Storage Tempurature Range: -65.0/+150.0 degrees celsius  Features Provided: Internally compensated and hermetically sealed and monolithic and electrostatic sensitive  Inclosure Material:
Operating Tempurature Range: -55.0/+125.0 degrees celsius  Storage Tempurature Range: -65.0/+150.0 degrees celsius  Features Provided: Internally compensated and hermetically sealed and monolithic and electrostatic sensitive Inclosure Material:
-55.0/+125.0 degrees celsius  Storage Tempurature Range: -65.0/+150.0 degrees celsius  Features Provided: Internally compensated and hermetically sealed and monolithic and electrostatic sensitive Inclosure Material:
Storage Tempurature Range: -65.0/+150.0 degrees celsius  Features Provided: Internally compensated and hermetically sealed and monolithic and electrostatic sensitive Inclosure Material:
-65.0/+150.0 degrees celsius  Features Provided: Internally compensated and hermetically sealed and monolithic and electrostatic sensitive Inclosure Material:
Features Provided: Internally compensated and hermetically sealed and monolithic and electrostatic sensitive Inclosure Material:
Internally compensated and hermetically sealed and monolithic and electrostatic sensitive  Inclosure Material:
Inclosure Material:
Metal
Inclosure Configuration:
Dual-in-line
Input Circuit Pattern:
2 input
Criticality Code Justification:
Feat
Design Function And Quantity:
1 amplifier, operational, general purpose
Case Outline Source And Designator:
A-2 mil-m-38510
Current Rating Per Characteristic:
4.20 milliamperes reverse current, dc absolute
Terminal Surface Treatment:
Solder
Product Name:
Voltage reglator
Voltage Rating And Type Per Characteristic:
-22.0 volts power source and 22.0 volts power source
Special Features:
Nuclear hardness critical item
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.)
Terminal Type And Quantity:
10 pin
Shelf Life:
N/a
Unit Of Measure:

## NSN 5962-01-374-0719

Linear Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0