NSN 5962-01-374-3085

Memory Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-374-3085

| View Online at https://aerobasegroup.com/nsn/5962-01-374-3085 |
|--|
| Operating Tempurature Range: |
| -55.0/+125.0 degrees celsius |
| Storage Tempurature Range: |
| -65.0/+150.0 degrees celsius |
| End Application: |
| 5840-01-229-1276 |
| Features Provided: |
| Programmed and 3-state output |
| Inclosure Configuration: |
| Dual-in-line |
| Case Outline Source And Designator: |
| D-2 mil-m-38510 |
| Product Name: |
| Microcircuit digital, 2048-bit read only memor (512 x 4) |
| Voltage Rating And Type Per Characteristic: |
| -0.5 volts total supply and 7.0 volts total supply and -0.5 volts absolute input and 5.5 volts absolute input and -0.5 volts absolute output |
| and 5.5 volts absolute output |
| Time Rating Per Chacteristic: |
| 60.00 nanoseconds access |
| Memory Device Type: |
| Prom |
| Hybrid Technology Type: |
| Monolithic |
| Test Data Document: |
| 81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And 96906-mil-std-883 |
| standard (includes industry or association standards, individual manufactureer standards, etc.). |
| Terminal Type And Quantity: |
| 16 printed circuit |
| Specification Data: |
| 56977-c5091143-1 manufacturers source control |
| Purchase Description Identification: |
| 56977-c5091206-1 |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

Fiig:

A458a0

Yes - demil/mli