NSN 5962-01-374-4819

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-374-4819
Body Length:
Between 4.800 inches and 5.000 inches
Body Width:
Between 3.800 inches and 4.000 inches
Body Height:
Between 1.450 inches and 1.680 inches
Operating Tempurature Range:
-40.0/+85.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
Scope shield e/i fscm 23386
Features Provided:
Low current and high frequency and gain controlled and low power
Inclosure Material:
Plastic
Inclosure Configuration:
Dual-in-line
Input Circuit Pattern:
2 input
Design Function And Quantity:
1 mixer, double balanced and 2 amplifier, linear and 1 oscillator and 1 regulator, voltage
Case Outline Source And Designator:
S0-8 joint electron device engineering council
Current Rating Per Characteristic:
2.40 milliamperes forward current, peak total value and 2.80 milliamperes average forward current averaged over a full 60-hz cycle
Terminal Surface Treatment:
Solder
Product Name:
Double-balanced mixer and oscillator
Voltage Rating And Type Per Characteristic:
9.0 volts total
Capitance Rating Per Characteristic:
3.00 output picofarads and 3.50 output picofarads
Special Features:
Small outline package
Terminal Type And Quantity:
8 printed circuit
Shelf Life:

--

N/a

Unit Of Measure:

NSN 5962-01-374-4819

Linear Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0