

View Online at <https://aerobasegroup.com/nsn/5962-01-374-5591>

Body Length:

Between 0.400 inches and 0.411 inches

Body Width:

Between 0.292 inches and 0.299 inches

Body Height:

Between 0.084 inches and 0.100 inches

Maximum Power Dissipation Rating:

500.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

Features Provided:

High performance and w/enable and w/switch and bidirectional and monolithic

Inclosure Material:

Plastic

Inclosure Configuration:

Dual-in-line

Input Circuit Pattern:

13 input

Design Function And Quantity:

1 multiplexer/demultiplexer, analog

Current Rating Per Characteristic:

160.00 microamperes reverse current, dc absolute

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

-0.5 volts power source and 14.0 volts power source

Capitance Rating Per Characteristic:

35.00 input pascal industrial light tank stock and 35.00 output pascal industrial light tank stock

Time Rating Per Chacteristic:

90.00 nanoseconds propagation delay time, high to low level output and 90.00 nanoseconds propagation delay time, low to high level output

Terminal Type And Quantity:

16 gullwing

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0