NSN 5962-01-374-5591

Linear Microcircuit - Page 1 of 1



view Online at https://aerobasegroup.com/hsh/5962-01-374-5591
Body Length:
Between 0.400 inches and 0.411 inches
Body Width:
Between 0.292 inches and 0.299 inches
Body Height:
Between 0.084 inches and 0.100 inches
Maximum Power Dissipation Rating:
500.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
High performance and w/enable and w/switch and bidirectional and monolithic
Inclosure Material:
Plastic
Inclosure Configuration:
Dual-in-line
Input Circuit Pattern:
13 input
Design Function And Quantity:
1 multiplexer/demultiplexer, analog
Current Rating Per Characteristic:
160.00 microamperes reverse current, dc absolute
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
-0.5 volts power source and 14.0 volts power source
Capitance Rating Per Characteristic:
35.00 input pascal industrial light tank stock and 35.00 output pascal industrial light tank stock
Time Rating Per Chacteristic:
90.00 nanoseconds propagation delay time, high to low level output and 90.00 nanoseconds propagation delay time, low to high level
output
Terminal Type And Quantity:
16 gullwing
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

Fiig:

A458a0

Yes - demil/mli