

View Online at <https://aerobasegroup.com/nsn/5962-01-374-5592>

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

End Application:

Target pod e/i fscm 04939

Features Provided:

Fast settling and monolithic

Inclosure Material:

Ceramic or glass or metal

Inclosure Configuration:

Leaded chip carrier

Input Circuit Pattern:

Quad 4 input

Design Function And Quantity:

4 amplifier, operational, linear

Terminal Surface Treatment:

Gold

Product Name:

Microcircuit linear, fastsettling operational amplifier

Voltage Rating And Type Per Characteristic:

-6.0 volts total supply and 6.0 volts total supply

Special Features:

Castellation lead connections

Precious Material And Location:

Castellation finish gold

Precious Material:

Gold

Test Data Document:

81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And 81349-mil-m-55565 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

20 printed circuit

Specification Data:

04939-717801057-001 manufacturers specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization: