NSN 5962-01-374-5597

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-374-5597

\mathbf{p}	4	 na	د ماء

Between 0.386 inches and 0.393 inches

Body Width:

Between 0.150 inches and 0.157 inches

Body Height:

Between 0.054 inches and 0.068 inches

Maximum Power Dissipation Rating:

500.0 milliwatts

Operating Tempurature Range:

-55.0/+125.0 degrees celsius

Storage Tempurature Range:

-65.0/+150.0 degrees celsius

End Application:

6625-01-286-3566

Features Provided:

Compatible cmos and compatible dtl and high noise and low current and tested to mil-std-883 and thermal overload protection

Inclosure Material:

Plastic

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Complementary-metal oxide-semiconductor logic

Input Circuit Pattern:

6 input

Design Function And Quantity:

8 decoder

Case Outline Source And Designator:

751b-03 joint electron device engineering council

Current Rating Per Characteristic:

-50.00 milliamperes collector cutoff current, dc, with specified resistance between base and emitter absolute and 50.00 milliamperes reverse current, dc absolute

Terminal Surface Treatment:

Solder

Product Name:

1-of-8 decoder/demultiplexer

Voltage Rating And Type Per Characteristic:

-0.5 volts total supply and 7.0 volts total supply

Special Features:

Small outline package

Terminal Type And Quantity:

16 printed circuit

Shelf Life:

N/a

NSN 5962-01-374-5597

Digital Microcircuit - Page 2 of 2



			ure:	

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0