

View Online at <https://aerobasegroup.com/nsn/5962-01-374-7255>

Body Width:

0.210 inches

Body Height:

0.500 inches

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

End Application:

Milstar e/i fscm 49956

Features Provided:

Hybrid and thin film and electrostatic sensitive

Inclosure Material:

Metal

Inclosure Configuration:

Can

Input Circuit Pattern:

1 input

Design Function And Quantity:

1 amplifier, hybrid

Current Rating Per Characteristic:

33.00 milliamperes forward current, nonrepetitive, peak total value absolute

Product Name:

Microcircuit, hybrid amplifier

Voltage Rating And Type Per Characteristic:

10.0 volts applied

Hybrid Technology Type:

Film

Special Features:

Rescreened for milstar

Test Data Document:

81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

4 printed circuit

Specification Data:

13499-252-0062-010 manufacturers specification control

Purchase Description Identification:

95105-rc252-0062-010

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fig:

A458a0