

View Online at <https://aerobasegroup.com/nsn/5962-01-374-7255>

**Body Width:**

0.210 inches

**Body Height:**

0.500 inches

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**End Application:**

Milstar e/i fscm 49956

**Features Provided:**

Hybrid and thin film and electrostatic sensitive

**Inclosure Material:**

Metal

**Inclosure Configuration:**

Can

**Input Circuit Pattern:**

1 input

**Design Function And Quantity:**

1 amplifier, hybrid

**Current Rating Per Characteristic:**

33.00 milliamperes forward current, nonrepetitive, peak total value absolute

**Product Name:**

Microcircuit, hybrid amplifier

**Voltage Rating And Type Per Characteristic:**

10.0 volts applied

**Hybrid Technology Type:**

Film

**Special Features:**

Rescreened for milstar

**Test Data Document:**

81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Terminal Type And Quantity:**

4 printed circuit

**Specification Data:**

13499-252-0062-010 manufacturers specification control

**Purchase Description Identification:**

95105-rc252-0062-010

**Shelf Life:**

N/a

**Unit Of Measure:**

**Demilitarization:**

Yes - demil/mli

**Fig:**

A458a0