

View Online at <https://aerobasegroup.com/nsn/5962-01-374-7260>

**Body Length:**

21.340 millimeters

**Body Width:**

Between 5.590 millimeters and 7.870 millimeters

**Body Height:**

5.080 millimeters

**Operating Temperature Range:**

-40.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**End Application:**

F15e aircraft e/i fscm 76301

**Features Provided:**

Bipolar and monolithic and 3-state output

**Inclosure Configuration:**

Dual-in-line

**Output Logic Form:**

Emitter-coupled logic

**Terminal Surface Treatment:**

Solder

**Product Name:**

Microcircuit, 64-bit ram tristate outputs

**Voltage Rating And Type Per Characteristic:**

-0.5 volts absolute input and 7.0 volts absolute input

**Time Rating Per Characteristic:**

32.00 nanoseconds access

**Memory Device Type:**

Ram

**Hybrid Technology Type:**

Monolithic

**Memory Capacity:**

Unknown

**Test Data Document:**

81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And 96906-mil-d-1000 standard (includes industry or association standards, individual manufactureer standards, etc.). And 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). And 96906-mil-std-130 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Terminal Type And Quantity:**

16 printed circuit

**Specification Data:**

55974-6414562-1 manufacturers specification control

**Shelf Life:**

N/a

**Demilitarization:**

No

**Fig:**

A458a0