

View Online at <https://aerobasegroup.com/nsn/5962-01-374-8572>

Body Length:

Between 0.930 inches and 0.970 inches

Body Width:

Between 0.245 inches and 0.310 inches

Body Height:

Between 0.140 inches and 0.175 inches

Maximum Power Dissipation Rating:

490.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Programmed and bidirectional and w/disable and w/enable and ultraviolet erasable and monolithic

Inclosure Material:

Ceramic

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Complementary-metal oxide-semiconductor logic

Input Circuit Pattern:

15 input

Current Rating Per Characteristic:

70.00 milliamperes reverse current, dc absolute

Terminal Surface Treatment:

Solder

Product Name:

And-or invert gate array

Voltage Rating And Type Per Characteristic:

7.0 volts power source

Capitance Rating Per Characteristic:

7.00 input picofarads and 7.00 output picofarads

Memory Device Type:

Pal

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

20 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A458a0