## NSN 5962-01-374-8573

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-374-8573

**Body Length:** 

Between 0.540 inches and 0.560 inches

**Body Width:** 

Between 0.442 inches and 0.458 inches

**Body Height:** 

0.105 inches

**Maximum Power Dissipation Rating:** 

1.0 watts

**Operating Tempurature Range:** 

-55.0/+125.0 degrees celsius

Storage Tempurature Range:

-65.0/+150.0 degrees celsius

**Features Provided:** 

Electrostatic sensitive and bidirectional and w/enable and w/inhibit and monolithic

**Inclosure Material:** 

Ceramic

**Inclosure Configuration:** 

Leadless flat pack

**Output Logic Form:** 

Complementary-metal oxide-semiconductor logic

**Input Circuit Pattern:** 

26 input

**Current Rating Per Characteristic:** 

60.00 milliamperes reverse current, dc absolute

**Terminal Surface Treatment:** 

Solder

**Voltage Rating And Type Per Characteristic:** 

-1.00 volts power source and 7.0 volts power source

**Capitance Rating Per Characteristic:** 

6.00 input picofarads and 10.00 output picofarads

Time Rating Per Chacteristic:

350.00 nanoseconds access

**Memory Device Type:** 

**Eeprom** 

**Special Features:** 

With 64-byte page write capability

**Test Data Document:** 

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Terminal Type And Quantity:** 

32 leadless

Shelf Life:

N/a

## NSN 5962-01-374-8573

Memory Microcircuit - Page 2 of 2



			ure:	

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0