## NSN 5962-01-374-9571

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-374-9571

**Body Length:** 

10.3 millimeters

**Body Width:** 

Between 5.6 millimeters and 7.9 millimeters

**Body Height:** 

3.6 millimeters

**Maximum Power Dissipation Rating:** 

400.0 milliwatts

**Operating Tempurature Range:** 

-55.0/+125.0 degrees celsius

Storage Tempurature Range:

-65.0/+150.0 degrees celsius

**End Application:** 

E3 trainer e/i fscm 1x380

**Features Provided:** 

Buffered reset and monolithic

**Inclosure Material:** 

Ceramic

**Inclosure Configuration:** 

Dual-in-line

**Design Function And Quantity:** 

1 comparator, voltage and 1 buffer

**Case Outline Source And Designator:** 

D-4 mil-m-38510

**Current Rating Per Characteristic:** 

50.00 milliamperes forward current, peak total value not applicable

**Terminal Surface Treatment:** 

Solder

**Product Name:** 

Voltage comparator

Voltage Rating And Type Per Characteristic:

-30.0 volts negative power supply span and 30.0 volts positive power supply span

**Test Data Document:** 

81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Terminal Type And Quantity:** 

8 printed circuit

Specification Data:

81349--38510/103 government specification

**Specification Or Standard:** 

04 type and b class and p case and a finish

Shelf Life:

. . .

## NSN 5962-01-374-9571

Linear Microcircuit - Page 2 of 2



ı	In	it I	Of	· M	دما	e i	ıre:
ι	JΝ	II '	ωı	IV	еа	SU	ıre:

--

Demilitarization:

No

Fiig:

A458a0