

View Online at <https://aerobasegroup.com/nsn/5962-01-375-0481>

**Maximum Power Dissipation Rating:**

400.0 milliwatts

**Operating Temperature Range:**

-40.0/+85.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**End Application:**

6625-01-275-6268

**Features Provided:**

Bidirectional and low power and compatible cmos and compatible dtl

**Inclosure Material:**

Plastic

**Inclosure Configuration:**

Dual-in-line

**Design Function And Quantity:**

1 driver, display crystal, liquid cmos

**Current Rating Per Characteristic:**

20.00 milliamperes reverse current, dc microamperes and 25.00 milliamperes average forward current averaged over a full 60-hz cycle not applicable

**Terminal Surface Treatment:**

Solder

**Product Name:**

Universal lcd driver

**Voltage Rating And Type Per Characteristic:**

-0.5 volts total supply and 11.0 volts total supply

**Special Features:**

Package=56-pin mini-pack (vso-56; sot-190)

**Terminal Type And Quantity:**

56 printed circuit

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A458a0