

View Online at <https://aerobasegroup.com/nsn/5962-01-375-1551>

Body Length:

Between 0.165 inches and 0.185 inches

Body Outside Diameter:

Between 0.335 inches and 0.375 inches

Maximum Power Dissipation Rating:

350.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

End Application:

6625-01-260-9326 test set, electronic systems

Features Provided:

Burn in and w/resistor and monolithic

Inclosure Material:

Metal

Inclosure Configuration:

Can

Input Circuit Pattern:

1 channel and 3 input

Design Function And Quantity:

1 switch, analog, single pole double throw and 1 driver, switch

Case Outline Source And Designator:

A-2 mil-m-38510

Current Rating Per Characteristic:

1.40 milliamperes reverse current, dc absolute

Terminal Surface Treatment:

Solder

Product Name:

Spdt switch, break-before-make

Voltage Rating And Type Per Characteristic:

-18.0 volts power source and 18.0 volts power source

Test Data Document:

81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

10 pin

Specification Data:

81349-mil-m-38510/111 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A458a0