

View Online at <https://aerobasegroup.com/nsn/5962-01-375-2539>

**Body Length:**

Between 1.230 inches and 1.280 inches

**Body Width:**

Between 0.245 inches and 0.310 inches

**Body Height:**

Between 0.095 inches and 0.185 inches

**Maximum Power Dissipation Rating:**

660.0 milliwatts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**Features Provided:**

3-state output and high speed and low power and w/disable and high performance and ultraviolet erasable and high impedance

**Inclosure Material:**

Ceramic

**Inclosure Configuration:**

Dual-in-line

**Output Logic Form:**

Complementary-metal oxide-semiconductor logic

**Input Circuit Pattern:**

14 input

**Current Rating Per Characteristic:**

120.00 milliamperes reverse current, dc absolute

**Terminal Surface Treatment:**

Solder

**Voltage Rating And Type Per Characteristic:**

-0.5 volts power source and 7.0 volts power source

**Capitance Rating Per Characteristic:**

5.00 input picofarads and 8.00 output picofarads

**Time Rating Per Chacteristic:**

45.00 nanoseconds access

**Memory Device Type:**

Eprom

**Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Terminal Type And Quantity:**

24 printed circuit

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A458a0