

View Online at <https://aerobasegroup.com/nsn/5962-01-375-3740>

Body Length:

1.060 inches

Body Width:

Between 0.220 inches and 0.310 inches

Body Height:

0.185 inches

Maximum Power Dissipation Rating:

541.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

End Application:

1440-01-087-9844 launching station, guided missile, semitrailer

Features Provided:

3-state output and high impedance and bipolar and w/enable

Inclosure Material:

Ceramic

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Complementary-metal oxide-semiconductor logic

Input Circuit Pattern:

9 input

Design Function And Quantity:

8 latch, d

Case Outline Source And Designator:

D-8 mil-m-38510

Current Rating Per Characteristic:

60.00 milliamperes reverse current, dc absolute

Terminal Surface Treatment:

Solder

Product Name:

D-type octal transparent latch

Voltage Rating And Type Per Characteristic:

-0.5 volts power source and 7.0 volts power source

Time Rating Per Characteristic:

10.30 nanoseconds propagation delay time, high to low level output and 10.10 nanoseconds propagation delay time, low to high level output

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

20 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A458a0