# NSN 5962-01-375-4456

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-375-4456

odv		

Between 1.270 inches and 1.290 inches

**Body Width:** 

Between 0.590 inches and 0.610 inches

**Body Height:** 

Between 0.205 inches and 0.225 inches

#### **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

#### **Storage Tempurature Range:**

-65.0/+150.0 degrees celsius

#### **End Application:**

Pacer special

#### **Features Provided:**

Burn in, mil-std-883, class b and electrostatic sensitive and monolithic and hermetically sealed and ultraviolet erasable and high speed and erasable and programmable and tested to mil-std-883

#### **Inclosure Material:**

Ceramic and glass and metal

#### **Inclosure Configuration:**

Dual-in-line

#### **Output Logic Form:**

Complementary-metal oxide-semiconductor logic

#### **Criticality Code Justification:**

Feat

#### **Case Outline Source And Designator:**

D-3 mil-m-38510

#### **Terminal Surface Treatment:**

Solder

#### **Product Name:**

Microcircuit, memory-eprom, 8k x 8, cmos, high speed, uv erasable

# **Voltage Rating And Type Per Characteristic:**

4.5 volts total supply and 5.5 volts total supply

## **Memory Device Type:**

**Eprom** 

#### **Special Features:**

Electrostatic discharge sensitive

#### **Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

### **Terminal Type And Quantity:**

24 printed circuit

#### Shelf Life:

N/a

#### **Unit Of Measure:**

--

# NSN 5962-01-375-4456

Memory Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0