

View Online at <https://aerobasegroup.com/nsn/5962-01-375-4964>

Body Length:

0.640 inches

Body Width:

Between 0.300 inches and 0.420 inches

Body Height:

Between 0.045 inches and 0.090 inches

Maximum Power Dissipation Rating:

1.02 watts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Programmed and w/active pull-up and 3-state output and high impedance and schottky and bipolar and w/enable and monolithic

Inclosure Material:

Ceramic

Inclosure Configuration:

Flat pack

Input Circuit Pattern:

14 input

Case Outline Source And Designator:

F-6 mil-m-38510

Current Rating Per Characteristic:

185.00 milliamperes reverse current, dc absolute

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

-0.5 volts power source and 7.0 volts power source

Time Rating Per Characteristic:

55.00 nanoseconds propagation delay time, high to low level output and 55.00 nanoseconds propagation delay time, low to high level output

Memory Device Type:

Prom

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

24 flat leads

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0