

View Online at <https://aerobasegroup.com/nsn/5962-01-376-1130>

Maximum Power Dissipation Rating:

377.0 milliwatts

Operating Temperature Range:

-40.0/+85.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

End Application:

Scope shield e/i fscm 23386

Features Provided:

Low drift and high impedance and low noise

Inclosure Material:

Plastic

Inclosure Configuration:

Dual-in-line

Design Function And Quantity:

1 amplifier, operational, linear

Current Rating Per Characteristic:

-5.00 milliamperes collector cutoff current, dc, with specified resistance between base and emitter microamperes and 5.00 milliamperes reverse current, dc microamperes and -30.00 milliamperes collector cutoff current, dc, base open not applicable and 30.00 milliamperes average forward current averaged over a full 60-hz cycle not applicable

Terminal Surface Treatment:

Solder

Product Name:

Programmable low-power operational amplifier

Voltage Rating And Type Per Characteristic:

4.0 volts total supply and 16.0 volts total supply

Special Features:

Small outline package

Terminal Type And Quantity:

8 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0