

View Online at <https://aerobasegroup.com/nsn/5962-01-376-1130>

**Maximum Power Dissipation Rating:**

377.0 milliwatts

**Operating Temperature Range:**

-40.0/+85.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**End Application:**

Scope shield e/i fscm 23386

**Features Provided:**

Low drift and high impedance and low noise

**Inclosure Material:**

Plastic

**Inclosure Configuration:**

Dual-in-line

**Design Function And Quantity:**

1 amplifier, operational, linear

**Current Rating Per Characteristic:**

-5.00 milliamperes collector cutoff current, dc, with specified resistance between base and emitter microamperes and 5.00 milliamperes reverse current, dc microamperes and -30.00 milliamperes collector cutoff current, dc, base open not applicable and 30.00 milliamperes average forward current averaged over a full 60-hz cycle not applicable

**Terminal Surface Treatment:**

Solder

**Product Name:**

Programmable low-power operational amplifier

**Voltage Rating And Type Per Characteristic:**

4.0 volts total supply and 16.0 volts total supply

**Special Features:**

Small outline package

**Terminal Type And Quantity:**

8 printed circuit

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A458a0