NSN 5962-01-376-1132

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-376-1132

Maximum Power Dissipation Rating:
500.0 milliwatts
Operating Tempurature Range:
55.0/+125.0 degrees celsius
Storage Tempurature Range:
65.0/+150.0 degrees celsius
End Application:
Scope shield e/i fscm 23386
Features Provided:
_ow power and high noise
nclosure Material:
Plastic
nclosure Configuration:
Dual-in-line
nput Circuit Pattern:
3 input
Design Function And Quantity:
6 inverter
Case Outline Source And Designator:
751a joint electron device engineering council
Current Rating Per Characteristic:
10.00 milliamperes collector cutoff current, dc, emitter open horsepower metric and 10.00 milliamperes peak forward surge current
norsepower metric
Terminal Surface Treatment:
Solder
Product Name:
Hex inverter
Voltage Rating And Type Per Characteristic:
0.5 volts total supply and 18.0 volts total supply
Special Features:
Triple diode protection on all inputs + small outline package
Terminal Type And Quantity:
14 printed circuit
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
Yes - demil/mli
Fiig:

A458a0