

View Online at <https://aerobasegroup.com/nsn/5962-01-376-1138>

**Maximum Power Dissipation Rating:**

500.0 milliwatts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**End Application:**

Scope shield e/i fscm 23386

**Features Provided:**

Low power and w/clock and w/reset and monolithic

**Inclosure Material:**

Plastic

**Inclosure Configuration:**

Dual-in-line

**Output Logic Form:**

Complementary-metal oxide-semiconductor logic

**Design Function And Quantity:**

2 register, shift, parallel out

**Case Outline Source And Designator:**

751b-03 joint electron device engineering council

**Current Rating Per Characteristic:**

-10.00 milliamperes input and 10.00 milliamperes input and -10.00 milliamperes output and 10.00 milliamperes output

**Terminal Surface Treatment:**

Solder

**Product Name:**

Dual 4-bit static shift register

**Voltage Rating And Type Per Characteristic:**

-0.5 volts total supply and 18.0 volts total supply

**Special Features:**

Small outline package

**Terminal Type And Quantity:**

16 printed circuit

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A458a0