

View Online at <https://aerobasegroup.com/nsn/5962-01-376-1141>

Maximum Power Dissipation Rating:

500.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

End Application:

Scope shield e/i fscm 23386

Features Provided:

Cascadable and w/schmitt trigger

Inclosure Material:

Plastic

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Complementary-metal oxide-semiconductor logic

Input Circuit Pattern:

6 input

Design Function And Quantity:

6 eliminator, bounce

Case Outline Source And Designator:

751g-01 joint electron device engineering council

Current Rating Per Characteristic:

-10.00 milliamperes collector cutoff current, dc, with specified resistance between base and emitter microamperes and 10.00 milliamperes reverse current, dc microamperes

Terminal Surface Treatment:

Solder

Product Name:

Hex contact bounce eliminator

Voltage Rating And Type Per Characteristic:

-0.5 volts total supply and 18.0 volts total supply

Special Features:

Small outline package

Terminal Type And Quantity:

16 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0